



## NetAstra SU 2450 D

### Subscriber Unit – NetAstra SU 2450 D

NetAstra SU 2450 D is a Subscriber Unit (SU), providing high capacity access connectivity of up to 50 Mbps net aggregate throughput.

NetAstra SU 2450 D supports 2.3 to 2.4 GHz and complies with FCC/IC & Universal regulations.

NetAstra SU 2450 D is connectorized for external antenna (2 xN-type).

### Product Highlights

- Up to 50 Mbps net aggregate throughput
- Long range – up to 40 km/25 miles
- Guaranteed Service Level Agreement (SLA) per SU
- Exceptional short and constant latency
- Advanced MIMO, OFDM and Diversity technologies
- Robust and reliable operation in tough conditions, extreme temperatures and non line-of-sight scenarios
- Ease of operation and maintenance



## Product Specifications

### Configuration

Architecture	Outdoor Unit Connectorized for external antenna (2 xN-type)
PoE to ODU Interface	Outdoor CAT-5e cable; Maximum cable length: 100 m for 10/100BaseT and 75 m for 1000BaseT

### Radio

Capacity	25 Mbps net aggregate throughput
Range	Up to 40 km / 25 miles
Channel Bandwidth	Configurable: 10, 20 and 40 MHz (for the default band)
Modulation	2x2 MIMO-OFDM (BPSK/QPSK/16QAM/64QAM)
Adaptive Modulation & Coding	Supported
DFS	Not Supported (for the default band)
Diversity	Supported
Max Tx Power	26 dBm
Duplex Technology	TDD
Error Correction	FEC k = 1/2, 2/3, 3/4, 5/6
Encryption	AES 128; FIPS 197; AES 256 optional (via Software License Key)
Bandwidth allocation	Configurable: Symmetric and Asymmetric
Support Indoor units	Netronics PoE devices
Layer 2	Hub Mode
QoS	Packet classification to 4 priority queues according to 802.1p and Diffserv
VLAN Support	802.1Q, QinQ, 4094 VLANS

### Supported Bands

Band	Channel BW 5 MHz	Channel BW 10 MHz	Channel BW 20 MHz	Channel BW 40 MHz	Radio Compliance
2.4 GHz FCC/IC*	-	2.407 - 2.467	2.402 - 2.472	2.392 - 2.482	FCC 47CFR Part 15.247; IC RSS-210
2.4 GHz Universal	-	2.302 - 2.477	2.297 - 2.482	2.287 - 2.492	Universal

\*Default Band

Mechanical	
ODU Dimensions	28(w) x 19.5(h) x 8(d) cm
ODU Weight	2.4 kg / 5.29 lbs
Power	
Power Feeding	Power provided over ODU-IDU cable
Power Consumption	<20 W
Environmental	
Operating Temperatures	-35°C to 60°C / -31°F to 140°F
Humidity	100% condensing, IP67 (totally protected against dust and against immersion up to 1 m)
Safety	
FCC/IC (cTUVus)	UL 60950-1, UL 60950-22, CAN/CSA C22.2 60950-1, CAN/CSA C22.2 60950-22
ETSI	EN/IEC 60950-1, EN/IEC 60950-22
EMC	
FCC	47 CFR Class B, Part15, Subpart B
ETSI	EN 300 386, EN 301 489-1, EN 301 489-4
CAN/CSA-CEI/IEC	CISPR 22-04 Class B



600-15 Allstate Parkway, Markham  
 Ontario, Canada  
 Tel: +1 (905) 415 4585  
 Email: info@netronics-networks.com

[Netronics-networks.com](http://Netronics-networks.com)