



NetAstra SU 5x50 D

Subscriber Unit – NetAstra SU 5x50 D

NetAstra SU 5x50 D is a Subscriber Unit (SU), providing high capacity access connectivity of up to 50 Mbps net aggregate throughput. NetAstra SU 5x50 D works with NetAstra AU 5x200 base station.

NetAstra SU 5x50 D supports from 4.9 to 6.0 GHz and complies with FCC, IC (Canada) WPC (India), MII (China) and Universal regulations.

NetAstra SU 5x50 D is connectorized for external antenna (2 xN-type).

Product Highlights

- Up to 50 Mbps net aggregate throughput
- Long range – up to 40 km/25 miles
- Guaranteed Service Level Agreement (SLA) per SU
- Outstanding short and constant latency
- Advanced MIMO, OFDM and Diversity technologies
- Robust and reliable operation in harsh conditions, extreme temperatures and non-line-of-sight scenarios
- Ease of operation and maintenance



Product Specifications

Configuration

Architecture	Outdoor Unit Connectorized for external antenna (2 xN-type)
PoE to ODU Interface	Outdoor CAT-5e cable; Maximum cable length: 100 m for 10/100BaseT and 75 m for 1000BaseT

Radio

Capacity	50 Mbps net aggregate throughput
Range	Up to 40 km / 25 miles
Channel Bandwidth	Configurable: 5, 10, 20 and 40 MHz (for the default band)
Modulation	2x2 MIMO-OFDM (BPSK/QPSK/16QAM/64QAM)
Adaptive Modulation & Coding	Supported
DFS	Not Supported (for the default band)
Diversity	Supported
Max Tx Power	25 dBm
Duplex Technology	TDD
Error Correction	FEC k = 1/2, 2/3, 3/4, 5/6
Encryption	AES 128; FIPS 197; AES 256 optional (via Software License Key)
Supported Indoor Units	Netronics PoE devices
Bandwidth allocation	Configurable: Symmetric and Asymmetric
Layer 2	Hub Mode
QoS	Packet classification to 4 priority queues according to 802.1p and Diffserv
VLAN Support	802.1Q, QinQ, 4094 VLANs

Supported Bands

Band	Channel BW 5 MHz	Channel BW 10 MHz	Channel BW 20 MHz	Channel BW 40 MHz	Radio Compliance
5.8 GHz FCC/IC*	5.7275 - 5.8475	5.725 - 5.850	5.725 - 5.850	5.725 - 5.850	FCC 47CFR Part 15.247; IC RSS-210
4.9 GHz FCC/IC	4.9425 - 4.9875	4.940 - 4.990	4.940 - 4.990	-	FCC 47CFR Part 90 Subpart Y; IC RSS-111
4.9 GHz Universal	4.8975 - 4.9925	4.895 - 4.995	4.890 - 5.000	4.880 - 5.000	Universal
5.0 GHz Universal	4.9975 - 5.1525	4.995 - 5.155	4.990 - 5.160	4.980 - 5.170	Universal
5.1 GHz Universal	5.1475 - 5.3375	5.145 - 5.340	5.140 - 5.345	5.130 - 5.355	Universal
5.2 GHz FCC/IC	5.2525 - 5.3475	5.255 - 5.345	5.255 - 5.345	5.255 - 5.345	FCC 47CFR Part 15.407; IC RSS-210
5.4 GHz FCC/IC	5.4775 - 5.7175	5.480 - 5.715	5.480 - 5.715	5.480 - 5.715	FCC 47CFR Part 15.407; IC RSS-210
5.4 GHz IC	5.4775 - 5.7175	5.480 - 5.715	5.480 - 5.715	5.480 - 5.715	IC RSS-210
5.4 GHz Universal	5.4725 - 5.7225	5.470 - 5.725	5.465 - 5.730	5.455 - 5.740	Universal
5.8 GHz WPC	5.8275 - 5.8725	5.825 - 5.875	5.825 - 5.875	5.815 - 5.885	WPC (India) G.S.R 38(E) dated 19 January, 2007 Notification
5.8 GHz MII	5.7375 - 5.8375	5.735 - 5.840	5.730 - 5.845	5.720 - 5.855	CMIIT RTA
5.9 GHz Universal	5.7275 - 5.9525	5.725 - 5.955	5.720 - 5.960	5.710 - 5.970	Universal
6.0 GHz Universal	5.6975 - 6.0525	5.695 - 6.055	5.690 - 6.060	5.680 - 6.070	Universal

* Default Band

Mechanical	
ODU Dimensions	28(w) x 19.5(h) x 8(d) cm
ODU Weight	2.4 kg / 5.29 lbs
Power	
Power Feeding	Power provided over ODU-IDU cable
Power Consumption	<20 W
Environmental	
Operating Temperatures	-35°C to 60°C / -31°F to 140°F
Humidity	100% condensing, IP67 (totally protected against dust and against immersion up to 1 m)
Safety	
FCC/IC (cTUVus)	UL 60950-1, UL 60950-22, CAN/CSA C22.2 60950-1, CAN/CSA C22.2 60950-22
ETSI	EN/IEC 60950-1, EN/IEC 60950-22
EMC	
FCC	47 CFR Class B, Part15, Subpart B
ETSI	EN 300 386, EN 301 489-1, EN 301 489-4
CAN/CSA-CEI/IEC	CISPR 22-04 Class B



600-15 Allstate Parkway, Markham
Ontario, Canada
Tel: +1 (905) 415 4585
Email: info@netronics-networks.com

Netronics-networks.com